



The Roll Top system

ROLL TOP FENCING

UTILISES USER FRIENDLY

TOP AND BOTTOM "ROLLED"

EDGES FOR ENHANCED

SAFETY AND RIGIDITY.

Benefits

Built in rigidity

The rolled beam profile at the top and bottom edge of each panel results in maximum rigidity.

Attractive - durable

High quality appearance, long life and low maintenance through the use of galvanised wire and high build bonded polyester coating.

Economical

3.025m post centres for maximum economy of labour and handling. Simple and rapid installation.

Versatile

Supplied as complete system with panels, posts and gates. Ideal for multi-lift erection for fence heights of 2.4m to 4.0m.

The principle feature of the fence is the unique and 'user friendly' rolled beam section on the top and bottom edge, acting as horizontal supports spanning between the posts. The

open mesh configuration is also decorative in appearance allowing excellent through visibility. These safety features therefore make Roll Top the ideal product for dog proof fence for playgrounds, play areas and parks, etc.



Panels

Mesh Pattern

150 x 50mm resistance welded at each intersection

Horizontal Wires

5mm diameter at 150mm centres

Vertical Wires

5mm diameter at 50mm centres

Panels are made from zinc coated wire to BS 443 .

Minimum zinc coat weight : 60 g/m² and polyester coated

Tickness 100 microns minimum

Recommended Post System

Twilfix 2000

- posts pitched at 3.025m centres
- Post size 60 x 60 x 2mm RHS
- 80 x 60 x 2.5mm RHS for multi-lift fences upto 4.0m high



utilise steel fixing brackets to secure panels to the front face of the post

I/V = 8.03 cm³

Accessories

Fixator

Universal bracket for fixing 2 panels into the inserts. Made from mild steel.

Colour : Black RAL 9005

Security bolt

Stainless steel, M8 dia. countersunk socket head bolt

Colour: Black RAL 9005

Plastic Washer

M8 dia.

Colour: Black RAL 9005

Coating techniques

Panels made out of galvanised wires (min. 40 g/m²). An adhesion coating is given for a perfect adhesion with the polyester coating (min. 100 micron).

The posts are polyester powder coated with a galvanised substrate in accordance with Euro norm 10147 (min. 60 micron).

Finish

colour coated black or green.

Other colours available on request.



THE ROLL TOP SYSTEM				
Fence Height m	PANELS		POSTS	
	Panel Size Height/Width mm	O/A Length	Number of fixings Inters	Number of fixings Corners
0.9	900 x 3000	1500	3	6
1.2	1200 x 3000	1800	4	8
1.5	1500 x 3000	2100	4	8
1.8	1800 x 3000	2500	5	10

Applications

Parks, schools, playgrounds & sport-stadia, airports, utilities: gas, water, electric & telecommunications.

